




**QUALITY
ESSENTIAL
DISTRIBUTION**

GOOD PEOPLE

SFX/OSP4-LSZH-GRY

OSP4 4pr 24AWG Overall Foil Screen 600V Grey

LSZH (9504) CPR:Eca



Cable Construction	4 Pairs
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 8(0.20mm ²)
Stranded Diameter (mm)	0.22
Insulation	LSZH
Insulation Thickness (mm)	0.28
Insulation Diameter (mm)	1.25 ±0.10
Insulation Colour(s)	Red,Black;White,Black;Green,Black;Blue,Black
Al-PET Shield	>=115%
Drain Wire	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	0.19 ±0.008 x 8
Jacket	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	6.80 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP4 4x2x24AWG Overall Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<79.00Ω/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation, panel wiring and RS232 applications.



**QUALITY
ESSENTIAL
DISTRIBUTION**
GOOD PEOPLE

www.qedgroup.co.uk

sales@qedgroup.co.uk

01772 336111