

### Model

### PSUIP 1x 2A 12VDC

Input Range	AC 100-240V rated 3Amp main fuse
Input Frequency	50/60Hz
Output Current	1 x 2A
Output Voltage	DC 12V
Fuse	Auto-reset PTC Fuse for each output, rated 2.5Amp
Surge Protected	Yes
Weight	0.5kgs
Case Type	Grey Polycarbonate
Operating Temp	- 10°C to 40°C
Storage Temp	- 20°C to +50°C
Operating Humidity	0% to 95% RH non condensing
Size	8cmx15cmx7.1cm (WxHxD)
IP Rating (when correctly installed)	IP66

### Model

### PSUIP 1X1A 24VAC

### PSUIP 1X3A 24VAC

### PSUIP 1X4A 24VAC

Input Range	AC 230V rated 3Amp main fuse	AC 230V rated 3Amp main fuse	AC 220V rated 3Amp main fuse
Input Frequency	50Hz	50Hz	50Hz
Output Current	1 x 1A	1 x 3A	1 x 4A
Output Voltage	24VAC	24VAC	24VAC
Fuse	Auto-reset PTC Fuse for each output, rated 1.35Amp	Auto-reset PTC Fuse for each output, rated 5Amp	Auto-reset PTC Fuse for each output, rated 5Amp
Surge Protected	Yes	Yes	Yes
Weight	1.0Kg	1.5Kg	2.8kg
Case Type	Grey Polycarbonate	Grey Polycarbonate	Grey Polycarbonate
Operating Temp	- 10°C to 40°C	- 10°C to 40°C	- 10°C to 40°C
Storage Temp	- 20°C to +50°C	- 20°C to +50°C	- 20°C to +50°C
Operating Humidity	0% to 95% RH non condensing	0% to 95% RH non condensing	0% to 95% RH non condensing
Size	9.5cmx25cmx6.2cm (WxHxD)	9.5cmx25cmx6.2cm (WxHxD)	15cmx27cmx8.9cm (WxHxD)
IP Rating (when correctly installed)	IP66	IP66	IP66

