



TP-Link EAP115-WALL wireless access point 300 Mbit/s White Power over Ethernet (PoE)



Brand : TP-Link

Product code: EAP115-WALL

Product name : EAP115-WALL

- Easy-mount construction allows installation into any standard EU-type data wall-box
- Compact, low-profile design fits discreetly with any existing interior style
- Free Auranet Controller Software enables administrators to easily manage hundreds of EAPs
- Support Power over Ethernet (802.3af) for convenient and affordable installation
- Enterprise class Wi-Fi security helps to decrease network security threats
- Captive portal provides one convenient method of authentication for Wi-Fi guests

300Mbps Wireless N Wall-Plate Access Point

TP-Link EAP115-WALL. Maximum data transfer rate: 300 Mbit/s, Maximum data transfer rate (2.4 GHz): 300 Mbit/s, Ethernet LAN data rates: 10,100 Mbit/s. Security algorithms: 802.1x RADIUS, HTTPS, WPA, WPA-PSK, WPA2, WPA2-PSK. Management protocols: SNMP, Telnet. Power consumption (typical): 2.8 W. Placement: Wall, Product colour: White

Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✗	Power consumption (typical)	2.8 W
Maximum data transfer rate *	300 Mbit/s	Design	
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	Placement *	Wall
Ethernet LAN data rates	10,100 Mbit/s	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3af, IEEE 802.3u	Cable lock slot	✗
Cabling technology	10/100Base-T(X)	Reset button	✓
Automatic channel selection	✓	LED indicators	✓
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna	
Rate limiting	✓	Antenna type *	Internal
Wireless isolation	✓	Antennas quantity	2
Quality of Service (QoS) support	✓	Antenna gain level (max)	1.8 dBi
Transmitting power	15 dBmW	Weight & dimensions	
Security		Width	86.8 mm
Security algorithms *	802.1x RADIUS, HTTPS, WPA, WPA-PSK, WPA2, WPA2-PSK	Depth	30.2 mm
MAC address filtering	✓	Height	86.8 mm
Number of SSID supported	8	Operational conditions	
Protocols		Operating relative humidity (H-H)	10 - 90%
Management protocols	SNMP, Telnet	Operating temperature (T-T)	0 - 40 °C
Management features		Storage temperature (T-T)	-40 - 70 °C
Web-based management	✓	Storage relative humidity (H-H)	5 - 90%
Ports & interfaces		Logistics data	
Ethernet LAN (RJ-45) ports *	2	Harmonized System (HS) code	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-SEP-2022. Prints or copies of Information are only valid on the printed Publication date