

### Features

- Powder Coated Steel Construction
- Mounting holes to mount the unit securely by its base
- The same models can be stacked and bolted together
- Vented both sides for improved airflow
- Easy cable access at rear, eg BNCs, IEC plugs and data cables
- VDC, LDVR1, LDVR1-F have added front vent for HDD ventilation
- LDVR1-F 1 x 12v fans expelling hot air from the cabinet @ 35CFM includes 12v PSU
- LDVR-F & LDVR3-F 2 X 12v fans expelling hot air from the cabinet @ 70CFM includes 12v PSU
- LDVR3 & LDVR3-F - removable lid for easy access especially for NVRs with additional cabling

**HAY-LDVR1**



**HAY-LDVR**



**HAY-LDVR3**



**HAY-LDVR3-F**

ENCLOSURE	DIEMENSIONS	DEPTH	WIDTH	HEIGHT	WEIGHT
<b>HAY-LDVR1</b>	External	445 mm	404 mm	120 mm	6.0 kg
	Internal	400 mm	400 mm	91 mm	
<b>HAY-LDVR1-F</b>	External	445 mm	404 mm	120 mm	6.3 kg
	Internal	400 mm	400 mm	91 mm	
<b>HAY-LDVR</b>	External	540 mm	510 mm	124 mm	7.9 kg
	Internal	510 mm	478 mm	103 mm	
<b>HAY-LDVR-F</b>	External	540 mm	510 mm	124 mm	7.9 kg
	Internal	510 mm	480 mm	103 mm	
<b>HAY-LDVR3</b>	External	565 mm	510 mm	170 mm	10 kg
	Internal	560 mm	506 mm	160 mm	
<b>HAY-LDVR3-F</b>	External	565 mm	510 mm	170 mm	10.2 kg
	Internal	560 mm	480 mm	160 mm	