



LO40HD4GE - Europe LO40HD4GG - Global

Wireless HD 4G PIR Camera with 40m Lens

OCULI HD is a battery-powered, standalone wireless PIR detector with a built-in HD camera and is now available with a long 40m out and 4m across PIR detection range and a camera field of view of 60°. This long-range model is particularly suited to detecting vehicles or assets across an extended area such as a car park or along a perimeter line.

Luminite Electronics Ltd.

2a Bellevue Road, London, N11 3ER

info@luminite.co.uk

020 8368 7887

Events are transmitted over the 4G mobile network for rapid visual verification. Units and sites can be self-monitored and controlled via the unique OCULi web portal. This portal is a full monitoring platform for use only with OCULi units. It allows users to view footage, add sites, change the unit settings, assign new users and keep track of SIMs and data usage. Battery status is also monitored, with alerts sent when close to depletion. Remote monitoring only is achieved using the OCULi mobile phone apps currently for iOS and Android.

OCULI HD can be used anywhere with a good 4G signal. We can provide a choice of SIMs for use in the UK and elsewhere as well as offering non-steered SIMs that will always use the strongest signal. All footage is stored on the cloud server for three months so it can be easily downloaded for prosecution purposes. Cloud user fees are included in the monthly SIM cost. Customers can use their own SIM with an applicable monthly server access charge.

Solar Panel CMS Monitoring Cellular Network Cloud Conjugate Systems Self-Monitoring Couling Secure Cloud Couling Self-Monitoring Couling Couling


A solar kit is available which facilitates additional features such as Live Streaming and requests for further footage. A horn speaker can provide a choice of audio challenges. You can configure a pre-recorded message or sound to play automatically on detection or, you can make a two-way voice call to initiate a live voice challenge.

The PIR settings are adjustable within the web portal, allowing the user to configure sensitivity, and/or gating and pulse counting, as well as the day/night threshold. OCULI HD is fully tamper protected with IR anti-masking, 3 axis inertia sensing and enclosure tampers.


Picture quality is selectable from VGA up to 5MP providing very high-quality images. A switchable IR-cut filter means you will see realistic colour images by day and still be able to see images in the dark by way of the powerful built in IR illumination up to 15 metres. The arming schedule can be set individually or site-wide for each day of the week and can be set and unset up to 3 times per day.

Basic Information Power Requirements 2 x 3.6v lithium D cells OR 2 x 3.7v rechargeable Li-ion (not supplied) Mobile Data 4G to dedicated cloud server **Battery Life** 6-9 months on 3.6v lithium D cells SIM Card BT roaming SIM as standard Weight 850g (without batteries) Operating Temperature -20°C to +60°C Range Mounting Height 2.4 to 4 meters Weather Rating IP66 Warranty 2 years

Dimensions 1



IR LED



Detector Information				
Motion Detector Type	Passive Infrared			
Sensor Type	Quad Pyro			
Lens Type	Fresnel			
Detection Range	40m x 4m			


IR Power	1 amp			
IR Distance	10 meters			
Transmitted Events				


Lighting Information

IR frequency 850nm

Camera Information		
Selectable Camera Resolution	640 x 480 1280 x 720 1920 x 1080 5MP	
Camera Lens	60° Telephoto	
Video Sequence	2 frames per second over 7 seconds	

Transmitted Events			
Low Battery			
Signal Strength			
TimeLine® Video			
Heart Beat			





Solar Kit	Horn Speaker	Magnetic Wall Bracket
Part Code: SOLARKIT	Part Code: HORNSPEAKER	Part Code: MAGMOUNT

Accessories

Lens Pattern