



TP-Link EAP245-KIT-5 wireless access point 1300 Mbit/s White Power over Ethernet (PoE)

Brand : TP-Link

Product code: EAP245-KIT-5

Product name : EAP245-KIT-5



- Simultaneous 450Mbps on 2.4GHz and 1300Mbps on 5GHz totals 1750Mbps Wi-Fi speeds
 - Supports Seamless Roaming so even video streams and voice calls are unaffected as users move between locations
 - Free cloud centralized management and Omada app for ultra convenience and easy management
 - Support Power over Ethernet(802.3at/802.3af) for convenient and affordable installation
 - Secure guest network along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies
 - Band Steering Automatically moves dual-band devices onto the wider 5GHz band for faster connections
 - Load balance ensures large numbers of users have smooth network experiences in high-density business networks
 - Supports management VLAN for an enhanced network management
- Kit 5x EAP245, 12.3W, IEEE 802.11ac/n/g/b/a, 2x RJ-45, 2.4/5 GHz

Features		Power	
2.4 GHz *	✓	Power consumption (typical)	12.3 W
5 GHz *	✓	Design	
Maximum data transfer rate *	1300 Mbit/s	Placement *	Ceiling, Wall
Frequency band	2.4, 5 GHz	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af	Cable lock slot	✓
Automatic channel selection	✓	Cable lock slot type	Kensington
MIMO	✓	Reset button	✓
MIMO type	Multi User MIMO	LED indicators	Power
Virtual LAN features	SSID-based VLAN assignment	Certification	CE, FCC, RoHS
Rate limiting	✓	Antenna	
Wireless isolation	✓	Antenna type *	Internal
Airtime Fairness (ATF)	✓	Antenna direction type	Omni-directional
Quality of Service (QoS) support	✓	Antenna features	Integrated antenna
Transmitting power	27 dBmW	Antenna gain level (max)	4 dBi
Security		Performance	
Security algorithms *	64-bit WEP, 128-bit WEP, 152-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
MAC address filtering	✓	Weight & dimensions	
Number of SSID supported	16	Width	206 mm
Port-based Network Access Control (PNAC)	✓	Depth	182 mm
Access Control List (ACL)	✓	Height	37 mm
Management features		Packaging content	
Web-based management	✓	Number of products included	5 pc(s)
Syslog	✓	AC adapter included	✓
		Mounting kit	✓
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	2	Operating relative humidity (H-H)	10 - 90%
DC-in jack	✓	Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%
Power			
Power over Ethernet (PoE) *	✓		
AC input voltage	12 V		
Input current	1.5 A		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-SEP-2022. Prints or copies of Information are only valid on the printed Publication date