



TP-Link AX3000 Wall Plate WiFi 6 Access Point

Brand : TP-Link

Product code: EAP650-WALL

Product name : AX3000 Wall Plate WiFi 6 Access Point

- Blazing-Fast AX3000 WiFi 6 Speeds:: Simultaneous 574 Mbps on 2.4 GHz and 2402 Mbps on 5 GHz totals 2976 Mbps WiFi speeds
 - Higher Network Efficiency: Deliver data to more devices at the same time with less lag
 - Complete In-Room WiFi Coverage: Guaranteed strong signals and corner-to-corner WiFi coverage
 - Gigabit Port: Connect wired devices with one downlink gigabit port
 - Centralized Cloud Management: Integrates into Omada SDN for cloud access and remote management
 - Secure Guest Network: Implement multiple authentication options (SMS/Facebook Wi-Fi/ Voucher) packed with high-quality wireless security technologies
 - Easy Installation and PoE Support: Easy-to-install design, compatible with 86 mm & EU & US standard junction box, and 802.3af/at PoE support
- 802.3af/at PoE, 802.11ax/ac/n/g/b/a, 2.4/5 GHz, 574/2402 Mbps, 86 × 86 × 42.6 mm



Features		Power	
2.4 GHz *	✓	Power consumption (typical)	11.5 W
5 GHz *	✓	Design	
Maximum data transfer rate *	3000 Mbit/s	Placement *	Wall
Maximum data transfer rate (5 GHz)	2402 Mbit/s	Product colour *	White
Ethernet LAN data rates	10,100,1000 Mbit/s	Reset button	✓
Frequency band	2.4/5 GHz	LED indicators	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af, IEEE 802.3at	Certification	CE, RoHS
		Antenna	
		Antenna type *	Internal
		Weight & dimensions	
VLAN support	✓	Width	86 mm
Rate limiting	✓	Depth	86 mm
Band steering	✓	Height	42.6 mm
Airtime Fairness (ATF)	✓	Packaging data	
Quality of Service (QoS) support	✓	Package type	Box
Security		Packaging content	
Security algorithms *	SNMP, SSH, WPA-Enterprise, WPA2-Enterprise	Number of products included	1 pc(s)
MAC address filtering	✓	Quick start guide	✓
Number of SSID supported	16	Operational conditions	
Remote Authentication Dial-In User Service (RADIUS)	✓	Operating relative humidity (H-H)	10 - 920%
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) ports *	2	Storage temperature (T-T)	-40 - 70 °C
Power		Storage relative humidity (H-H)	5 - 90%
Power over Ethernet (PoE) *	✓		



Rate limit exceeded: Agreement for
bulk barcode creation required
<https://tec-it.com> # sales@tec-it.com



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.