

TP-Link LS1005G network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Brand : TP-Link **Product code:** LS1005G

Product name: LS1005G



- 5× 10/100/1000Mbos Auto-Negotiation RJ45 port, supporting Auto-MDI/MDIX
- Green Ethernet technology saves power
- IEEE 802.3X flow control provides reliable data transfer
- Plastic casing, desktop or wall-mounting design
- Plug and play, no configuration needed
- Fanless design ensures quiet operation

LS1005G, IEEE 802.3i/802.3u/ 802.3ab/802.3x, 5x 1G RJ-45, 10 Gbps, 7.4 Mpps, 90x72x23 mm TP-Link LS1005G. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 5 V. Wall mountable



Management features Switch type * Ports & interfaces	Unmanaged	Design International Protection (IP) code	IP20, IP40
21	Unmanaged	International Protection (IP) code	IP20 IP40
Danta C intenferen			11 20, 11 70
Ports & interfaces		Wall mountable	✓
Basic switching RJ-45 Ethernet ports	5	Certification	CE, FCC, RoHS
quantity *	3	Power	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included * DC input voltage	√ 5 V
Network		Input current	0.6 A
Networking standards *	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power consumption (max)	3.7 W
10G support *	×	Power over Ethernet (PoE)	
Flow control support	7	Power over Ethernet (PoE) *	X
Auto MDI/MDI-X	✓	Operational conditions	
Auto-negotiation	1	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-40 - 70 °C
Switching capacity *	10 Gbit/s	Operating relative humidity (H-H)	10 - 90%
Forwarding rate	7.4 Mpps	Storage relative humidity (H-H)	5 - 90%
MAC address table *	2000 entries	Heat dissipation	12.617 BTU/h
Store-and-forward	1	Weight & dimensions	
Jumbo frames support Jumbo frames	16000	Width	90 mm
Packet buffer memory	1.5 MB	Depth	72 mm
•	1.5 146	Height	23 mm
Design		Packaging data	
Rack mounting *	X	Quick start guide	✓
Product colour	Black Plastic	Package type	Box
Housing material LED indicators	Mastic ✓	Logistics data	
		Harmonized System (HS) code	85176990



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.