

TALOS SINGLE PHASE LINE I INTERACTIVE UPS



Technical Data Sheet

Model		T36 (205-0260)	T60 (205-0262)	T90 (205-0388)
Power	VA	650VA	1000VA	1600VA
	W	360W	500W	900W
Input	Related Voltage	160 – 290 Vac		
	Frequency	45 – 65 Hz		
Output	Related Voltage	220/230/240 Vac +/- 10%		
	Frequency on Battery Power	50/60 Hz +/- 1Hz		
	Waveform	Pseudo-sine wave		
	Output Sockets	1 IEC – C13 + 1 Schuko	3 IEC-C13 + 2 Schuko	
General	Dimensions (DxWxH) mm	100x292x140		148x315x198
	Weight (Kg)	5	5.5	10.5
	Alarms	Audible & Visual alarms		
	Protection	Overload, Short Circuit, deep discharge, overcharge		
	Plug in battery charging feature	Standard across all models		
	Cold Start from battery without mains	Standard across all models		
Battery	Number and Battery Types		12V VRLA, AGM (maintenance free lead)	
			1 of 12V	2 of 12V
	Up time with internal battery (mins)	50% Load	4 Mins	4 Mins
75% Load		1 Min	1 Min	5 Mins
Connectivity	Communication Ports		USB	
	User Interface		LCD Displaying: Operating Mode, Battery Charge level, Input & Output Voltage, Percentage load, Fault, near end of battery life.	
	Compatible software Platforms		Microsoft Windows, Linux, Mac	
Environmental conditions	Operating Temperature		0 – 40deg C	
	Relative Humidity		0% - 90% (without condensation)	
Regulations	Standards		IEC EN 62040-1, IEC EN 62040-2, IEC EN 62040-3	
	Marking		CE, UKCA	

Rear Views

